


Ditron



Kyla

OMEGA balance





TECHNICAL SPECIFICATIONS

Customer and Operator displays:

- numerical, LCD technology
- 7 segments
- 5 digits for the weight, 6 digits for the price, 6 digits for the amount
- 11 captions

Keyboard:

- 36 keys

Printer:

- max speed 60 mm/sec
- paper roll size: 58 mm x 30 mt

Low tension power supply:

- 110-230 V AC with external adapter 9V 2,5A
- 12V/24 V with (optional) **Join Plus** adapter

Consumption:

- ~ 25W

Connection:

- 1 serial port (RS232)

Maintenance:

- the whole electronic section is protected by a metrical seal. Free access is only allowed to the bottom of the scale and to custome display.

BASIC FUNCTIONS

Simultaneous operators:

4

PLU

- total PLU: 100
- direct PLU: 10
- semi-direct PLU: 10
- PLU with ingredients: 30 (with 5 lines of ingredients)

Traceability:

list (20 lists with 5 lines)

Operational modes:

- only weight
- receipt

Main features:




- programmable barcode printing
- recall of the subtotal and re-opening of the transaction
- void of the current transactions
- direct code programming or programming supported by menu and help
- totalizers printing (by item and by operator)
- sales report by VAT.

Connections:

serial ECR and PC connection (for software upgrade and data transfer)

Metric Versions

Capacity (max)	12 Kg	30 Kg	12/30 Kg
Division (e)	2 g	5 g	2/5 g
No of Divisions	6.000	6.000	Multirange
Tare (T=)	-9,998 Kg	-9,998 Kg	-9,998 Kg



DITRON Srl

Via Antiniana, 115 - 80078 Pozzuoli - Napoli - Italy

tel. +39 081 2428557 - fax +39 081 2428552

www.ditron.net - ditron@ditron.net



UNI EN ISO 9001:2000
num 9105.MICR

RIVENDITORE AUTORIZZATO