


compact *lite*




-  **DOUBLE SCALE CAPACITY**
-  **GREAT COMPUTING POWER**
-  **HIGH PERFORMANCE HARDWARE**
-  **BATTERY BACKUP**
-  **COLOR DISPLAY TFT 5,7"**
-  **HIGH RESOLUTION THERMAL HEAD 2'**

**INTINERANT
VERSION
AVAILABLE**



*compact
lite*



W41XD49XH65cm



W41XD53XH20cm

compact *lite* MAIN FEATURES

	LITE PL	LITE CS
Scale capacity	Multirange 12/30 kg - 2/5 g Multirange 6/15 kg - 2/5 g	
Load cell	30 kg 6000 div. multirange 15kg 3000 div. multirange	
Operator interface	89 waterproof mechanical keys color display TFT 5,7" resolution 320x240 px or with LED back-lit	
Customer display	color display TFT 5,7" resolution 320x240 px with LED back-lit	
PLU	56 PLU directs - 4 operators	
Printer	High resolution thermal head 2' core roll: 40 mm roll diameter: 90 mm roll width min 58mm max 62mm paper label position sensor (paper end/label alignment)	
Storage expansion	integrated	
Connections	2 ports RS232 on DB9 + 1 LAN/Ethernet + 1 USB for updating software	
Power supply	230 Vca (+10%-15%) battery backup (24V 1,2 A)	

* THE ITINERANT VERSION IS AVAILABLE BOTH MANUFACTURED AND WITH KIT TO BE INSTALLED ON SITE.

N.B. : By replacing the connection card it is possible to transform a Compact LITE into a ITINERANT Compact LITE! The transformation procedure must be carried out by a user with technical training.

