







compact *lite*



PL


-  **DUAL WEIGHING CAPACITY**
-  **GREAT COMPUTING POWER**
-  **HIGH PERFORMANCE HARDWARE**
-  **BACKUP BATTERY**
-  **COLOR DISPLAY 5,7" TFT**
-  **HIGH RESOLUTION 2" THERMAL HEAD**

**INTINERANT
VERSION
AVAILABLE**



CS

compact
lite



D41XW49XH65cm



D41XW53XH20cm

compact *lite* MAIN FEATURES

	LITE PL	LITE CS
Weighing range	Multirange 12/30 kg - 2/5 g Multirange 6/15 kg - 2/5 g	
Load cell	30 kg 6000 div. multirange 15kg 3000 div. multirange	
Operator interface	89 waterproof mechanical keys color display 5.7" TFT resolution 320x240 px with LED backlight	
Customer display	color display 5.7" TFT resolution 320x240 px with LED backlight	
PLU	56 PLU directs - up to 10000 PLU 4 operators	
Printer	2" high resolution thermal head roll core : 40 mm roll diameter: 90 mm roll width: min 58mm - max 62mm label position sensor (paper end/label alignment)	
Connections	2 RS232/DB9 + 1 Ethernet + 1 USB for software updating	
Operating voltage	230 Vca (+10%-15%) via mains power supply unit backup battery (24V 1,2 A)	

* THE EXTERNAL BATTERY CONNECTION AVAILABLE FOR ITINERANT VERSION

NOTE: it is possible to upgrade Compact LITE to itinerant version by replacing the connection board.
The procedure must be carried out by technical person only.

